

DataGuard® (SWA)

LSZH FireFighter® 440Series Multi-Pair

24awg Low Capacitance 600V



Cable Design

Core

Conductor	Stranded tinned copper wire (24awg)
Insulation	see specification table

Pair

2 cores twisted to a pair

Assembly

Centre	X pairs stranded
No. of Pairs	1, 2, 3, 4 or 8
Pair identification	Chart 5
Drain Wire	Stranded tinned copper wire
Shield	Overall Aluminium/polyester tape
Braid	Tinned copper wire braid, 90% coverage

Inner Jacket

LSZH FireFighter® SHF-1

Colour Grey RAL 7001

Armour

DataGuard® Steel Wire Armour (DSWA)

Outer Jacket

LSZH FireFighter® SHF-1

Colour Black

Characteristics

- Flame Retardant acc. to IEC 60332-1 flame resistance for single cables
- Flame Retardant acc. to IEC 60332-3 flame resistance for bunched cables
- Halogen Free acc. to IEC 60754 series
- Smoke Emission acc. to IEC 61034 series
- UV Stable
- 600 V Rated
- Temperature Range : -20°C to +90°C



DataGuard® (SWA)

LSZH FireFighter® 440Series Multi-Pair 24awg Low Capacitance 600V

Specification

Part Number	Formation <i>No. of Pairs</i>	Insulation	Insulation Diameter <i>mm</i>	Nom. Inner Jacket Ø <i>mm</i>	Nom. Outer Jacket Ø <i>mm</i>	Weight <i>kg/km</i>
144401P2454	1 x 2 x 24 awg	PE	1,62	5,00	10,00 ± 0,4	336
144402P2454	2 x 2 x 24 awg	PE	1,62	7,60	12,20 ± 0,4	350
144403P2454	3 x 2 x 24 awg	PE	1,62	8,20	12,30 ± 0,4	358
144404P2454	4 x 2 x 24 awg	PE	1,62	9,80 ± 0,3	14,00 ± 0,5	367
144408P2454	8 x 2 x 24 awg	Foam PE	1,15	9,10	13,15 ± 0,4	406

Electrical Characteristics

Nom. Capacitance (cond./cond.) <i>pF/m</i>	Nom. Capacitance (cond./cond./ screen) <i>pF/m</i>	Electrical Resistance <i>Ω/km</i>	Nom. Velocity of Propagation <i>%</i>	Nom. Inductance <i>μH/m</i>	Nom. Impedance <i>Ω</i>
42	75,5	82	66	0,56	120

Also available with DataGuard® armoured protection :



DataGuard® GSWB

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact details can be confirmed at point of enquiry