

3092F Coax - ControlNet™ and ControlBus™ Quad Shielded Coax



For more Information
please call

1-800-Belden1



General Description:

20 AWG stranded (105x40) bare copper conductor, foam polyethylene insulation, Duobond IV® quad shield (100% coverage), PVC Jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	20	105x40	BC - Bare Copper	1.016

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
FPE - Foam Polyethylene	4.6482

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100.000
2		Braid	AL - Aluminum	60.000
3	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100.000
4		Braid	AL - Aluminum	40.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 7.696 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +75°C

Bulk Cable Weight: 59.528 Kg/Km

Max. Recommended Pulling Tension: 155.687 N

Min. Bend Radius/Minor Axis: 76.200 mm

Min. Flexing Radius: 15.240 cm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CL2R, CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

METRIC MEASUREMENT VERSION

3092F Coax - ControlNet™ and ControlBus™ Quad Shielded Coax

RG Type: 6/U

Flame Test

UL Flame Test: UL1666 Riser

CSA Flame Test: FT4

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

75

Nom. Inductance:

Inductance (µH/m)

0.354348

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)

55.777

Nominal Velocity of Propagation:

VP (%)

79

Nominal Delay:

Delay (ns/m)

4.23249

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

34.4505

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

11.8116

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1	1.18116
2	1.54207
5	2.6248
10	3.9372
20	6.562
50	10.4992
100	15.0926
200	21.3265
300	26.248
400	30.5133

Other Electrical Characteristic 1:

IEEE 802.4 MAP/IEEE 802.7 Mini-Map

Shield Effectiveness:

Description	Freq. (MHz)	Effectiveness (dB)
Unflexed	30	92
After 1.5 million flexes	30	60

Minimum Structural Return Loss:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Min. SRL (dB)
		5	400	23

Notes (Overall)

Notes: CPE Jacket optional. Flex Life: 1.5 Million cycles @ 6.0" minimum bend radius. For Rockwell authorized Flexible ControlNet order YR28890 (Tinned Copper Braid Version).

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3092F 0101000	1,000 FT	33.000 LB	BLACK		#20 GIFHDLPE DBSH PVC
3092F 0105000	5,000 FT	170.000 LB	BLACK	C	#20 GIFHDLPE DBSH PVC

Notes:

C = CRATE REEL PUT-UP.

METRIC MEASUREMENT VERSION

3092F Coax - ControlNet™ and ControlBus™ Quad Shielded Coax

Revision Number: 1 Revision Date: 04-11-2008

© 2016 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).