


Armada[®] Profibus PA Offshore Cable SHF-1 UV

Cable Design

Conductor	Solid Bare Cu-wire, 1/1,05mm (18awg)
Insulation	Foamed Polyethylene (PE) with skin
Diameter	Ø 2,55 mm
Cable Core	2 cores twisted to a pair, Red and Green
Tape	Plastic tape, overlapped
EasyStrip Jacket	Thermoplastic copolymer, Ø 5,4 mm
Screen	Aluminium foil overlapped, applied longitudinally
Shield	Tinned copper wire braid 0.15 mm wires coverage 85 %
Inner Jacket	LSZH FireFighter [®]
Diameter	Ø 8,0 ± 0,40 mm
Armour	DataGuard [®] Galvanised Steel Wire Braid (GSWB)
Outer Jacket	LSZH FireFighter [®] SHF-1, UV-resistant
Diameter	Ø 10,65 ± 0,40 mm
Weight	386 kg/km



Application

Fixed installation on and below deck of commercial ships and offshore units. The cables meet the technical requirements of IEC 60092.

Standards

Flamability Rating	IEC 60332-1-2, IEC 60332-3-24, IEC 60754-1/2, IEC 61034
--------------------	---

Specification

Part Number	Outer Jacket Colour
24L45467-J20-C46	Black
24L45467-J20-C86	Blue (for I.S. Applications)

Electrical Data @ 20° C

Conductor resistance		≤	22	0hm/km
Insulation resistance		≥	10	M0hm*km
Capacitance (1 kHz wire/wire)		≈	50	nF/km
Capacitance (1 kHz wire/screen)		≈	92	nF/km
Operating voltage		≤	100	V
UL-Rating			600	V
Test Voltage (wire/wire/screen rms 50 Hz 1min)			2000	V
Characteristic Impedance	31,25 MHz		100±20	0hm
Attenuation	39 kHz	≤	3	dB/km
Capacitance Unbalance e		≤	2	nF/km
Inductance (31,25 kHz)			650	μH/km
Surface transfer impedance (20 MHz)		≤	5	m0hm/m
Rel. Velocity of Propagation		≈	81	%

Mechanical & Thermal Characteristics

Tempearture range		-20 to +80	°C
Min. Bending Radius	repeated	10	x Ø
	single	5	x Ø