



For more Information
please call

1-800-Belden1



General Description:

22 AWG stranded (7x30) tinned copper conductors, Datalene® insulation, twisted pairs, overall Beldfoil® shield (100% coverage) plus a tinned copper braid (65% coverage), drain wire, UV resistant PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
1	1	22	7x30	TC - Tinned Copper	0.762

Total Number of Conductors: 3

Insulation

Insulation Material:

Insulation Trade Name	Insulation Material
Datalene®	FHDPE - Foam High Density Polyethylene

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100.000
2		Braid	TC - Tinned Copper	65.000

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
22	7x30	TC - Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Cabling Color Code Chart:

Number	Color
1	White/Orange Stripe
2	Orange/White Stripe
3	Blue/White Stripe

Overall Nominal Diameter: 7.620 mm

Pair

Pair Lay Length & Direction:

Lay Length (mm)
76.2

Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +60°C
Non-UL Temperature Rating:	60°C
Bulk Cable Weight:	78.875 Kg/Km
Max. Recommended Pulling Tension:	289.133 N
Min. Bend Radius/Minor Axis:	76.200 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CM, PLTC
CEC/C(UL) Specification:	CM
EU Directive 2011/65/EU (ROHS II):	Yes

METRIC MEASUREMENT VERSION

3106A Multi-Conductor - EIA Industrial RS-485 PLTC/CM

EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
CSA Flame Test:	FT1

Suitability

Sunlight Resistance:	Yes
Oil Resistance:	Yes - Oil Res II

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Surface Printing (Overall)

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Description

120

Nom. Inductance:

Inductance (µH/m)

0.666043

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

36.091

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)

68.5729

Nominal Velocity of Propagation:

VP (%)

78

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

48.2307

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

9.1868

Nom. Attenuation:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Attenuation (dB/100m)
	1			1.6405

Max. Operating Voltage - UL:

Voltage

300 V RMS (NEC Type PLTC)

300 V RMS (NEC Type CM)

Max. Recommended Current:

Current

2.7 Amps per conductor @ 25°C

Other Electrical Characteristic 1: Input Impedance/Unfitted Impedance .5 - 10 MHz, 120 +/-12 Ohms

Notes (Overall)

Notes: Oil Resistance: Passes Oil Res II Per UL1277, Table 10.17. For CPE jacketed version order YR46721.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
3106A 0101000	1,000 FT	52,000 LB	BLACK	C	#22 FS PR,1#22PVCBRDPVC

Detailed Specifications & Technical Data



METRIC MEASUREMENT VERSION

3106A Multi-Conductor - EIA Industrial RS-485 PLTC/CM

3106A 010500	500 FT	27.000 LB	BLACK	C	#22 FS PR,1#22PVCBRDPVC
3106A 0105000	5,000 FT	255.000 LB	BLACK	C N	#22 FS PR,1#22PVCBRDPVC

Notes:

C = CRATE REEL PUT-UP.

N = FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.

Revision Number: 4 Revision Date: 01-06-2016

© 2016 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).