

## 7958A Multi-Conductor - Category 5e DataTuff® 600V AWM Rated Twisted Pair Cable



For more Information  
please call

1-800-Belden1



### General Description:

24 AWG Bonded-Pairs solid bare copper conductors, polyolefin insulation, overall Beldfoil® shield (100% coverage), industrial grade sunlight- and oil-resistant PVC jacket, drain wire, rip cord. Sequential marking at two foot intervals

### Usage (Overall)

**Suitable Applications:** Industrial Ethernet Cable, Harsh Environments, 200MHz Category 5e, Industrial Ethernet, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments, CMX - Outdoor, RJ-45 Compatible\*

### Physical Characteristics (Overall)

#### Conductor

**AWG:**

# Pairs	AWG	Stranding	Conductor Material
4	24	Solid	BC - Bare Copper

**Total Number of Conductors:** 8

#### Insulation

**Insulation Material:**

Insulation Material	Wall Thickness (mm)
PO - Polyolefin	0.254

#### Outer Shield

**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire	Conductor Material
24	7x32	TC - Tinned Copper	

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

**Outer Jacket Ripcord:** No

### Overall Cable

**Overall Nominal Diameter:** 6.731 mm

### Pair

**Pair Color Code Chart:**

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

### Mechanical Characteristics (Overall)

**Installation Temperature Range:** -25°C To +75°C

**Operating Temperature Range:** -40°C To +75°C

**Bulk Cable Weight:** 47.622 Kg/Km

**Max. Recommended Pulling Tension:** 155.687 N

**Min. Bend Radius/Minor Axis:** 12.700 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

**CEC/C(UL) Specification:** CMR

## 7958A Multi-Conductor - Category 5e DataTuff® 600V AWM Rated Twisted Pair Cable

AWM Specification:	UL Style 21047
EU Directive 2011/65/EU (ROHS II):	Yes
Other Standards:	TIA 1005
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Other Specification:	NEMA WC-63.1 Category 5e, UL verified to Category 5e, EtherNet/IP Compliant

**Applicable Patents:**

Country
<a href="http://www.belden.com/p">www.belden.com/p</a>

**Flame Test**

UL Flame Test:	UL1666 Riser
CSA Flame Test:	FT4
IEEE Flame Test:	1202

**Suitability**

Suitability - Outdoor:	Yes
Sunlight Resistance:	Yes
Oil Resistance:	Yes

**Plenum/Non-Plenum**

Plenum (Y/N):	No
---------------	----

### Electrical Characteristics (Overall)

**Nom. Mutual Capacitance:**

Capacitance (pF/m)
49.215

Maximum Capacitance Unbalance (pF/100 m):	150
---	-----

**Nominal Velocity of Propagation:**

VP (%)
70

**Maximum Delay:**

Delay (ns/100 m)
538 @ 100MHz

**Max. Delay Skew:**

Delay Skew (ns/100 m)
45

**Maximum Conductor DC Resistance:**

DCR @ 20°C (Ohm/100 m)
9.38

**Max. Operating Voltage - UL:**

Voltage	Description
300 V RMS	
600 V RMS	Appliance Wiring Material

**Maximum DCR Unbalanced:**

DCR Unbalance @ 20°C (%)
3

### Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)	Min. SRL (dB)
1	2.000	65.3	62.3	63.0	60.0	20.000	20.0
4	4.100	56.3	53.3	51.0	49.0	23.600	23.6
8	5.800	51.8	48.8	46.0	43.0	25.400	25.4
10	6.500	50.3	47.3	43.0	41.0	26.000	26.0

## METRIC MEASUREMENT VERSION

### 7958A Multi-Conductor - Category 5e DataTuff® 600V AWM Rated Twisted Pair Cable

16	8.200	47.3	44.3	39.0	36.0	26.000	26.0
20	9.300	45.8	42.8	36.5	33.5	26.000	26.0
25	10.400	44.3	41.3	33.9	30.9	25.500	25.5
31.25	11.700	42.9	39.9	31.0	28.0	25.000	25.0
62.5	17.000	38.4	35.4	22.0	19.0	23.500	23.5
100	22.000	35.3	32.3	14.0	11.0	22.500	22.5
200	32.400		27.8		1.0		

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	63.8	60.8
4	100 ± 15	100 ± 15	51.7	48.7
8	100 ± 15	100 ± 15	45.7	42.7
10	100 ± 15	100 ± 15	43.8	40.8
16	100 ± 15	100 ± 15	39.7	36.7
20	100 ± 15	100 ± 15	37.7	34.7
25	100 ± 15	100 ± 15	35.8	32.8
31.25	100 ± 15	100 ± 15	33.9	30.9
62.5	100 ± 15	100 ± 15	27.8	24.8
100	100 ± 15	100 ± 15	23.8	20.8
200	100 ± 25			14.7

#### Notes (Overall)

**Notes:** EtherNet/IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vender Association, Inc. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581. \*Special RJ45 plug required. See WWW. BELDEN.COM - Tools - Connector Cross Reference. Not intended for 600 V electrical power delivery.

#### Notes (Cont'd.):

T568A Plug Compatible Part Number: R301601 T568B Plug Compatible Part Number: R301602

#### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
7958A 0021000	1,000 FT	37.000 LB	RED	C	4 PR #24 PP FS FRPVC
7958A 0061000	1,000 FT	37.000 LB	BLUE, LIGHT	C	4 PR #24 PP FS FRPVC
7958A 0081000	1,000 FT	37.000 LB	GRAY	C	4 PR #24 PP FS FRPVC
7958A 0101000	1,000 FT	37.000 LB	BLACK	C	4 PR #24 PP FS FRPVC
7958A 0102000	2,000 FT	68.000 LB	BLACK		4 PR #24 PP FS FRPVC
7958A 1NH1000	1,000 FT	37.000 LB	TEAL 1NH	C	4 PR #24 PP FS FRPVC

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 0 Revision Date: 07-19-2016

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.