


PRODUCT CODE: MSEC C64PEXT GEL

CAT6 4 Pair UTP 23AWG, External, Gel Filled, Network Cable



APPLICATION	External / Direct Bury High Speed Data / Communication Network 100Base-TX, 100Base-T, 100VG-AnyLAN, 1000Base-T (Gigabit Ethernet), 1000Base-TX, ATM
CONDUCTOR	Solid Bare Copper 23AWG $\varnothing = 0.57\text{mm} \pm 0.005$
INSULATION	HDPE Colour: Pair 1: White / Blue & Blue, Pair 2: White / Orange & Orange, Pair 3: White / Green & Green Pair 4: White / Brown & Brown $\varnothing = 1.02\text{mm} \times 4 \text{ Pair}$
JELLY FILLED	Yes
RIP CORD	Yes
OUTER JACKET	PE – Polyethylene Colour: Black
NOMINAL O.D (mm)	$\varnothing = 6.5\text{mm} \pm 0.10\text{mm}$
CABLE MARKING	MASER 4PAIR UTP CAT6 GEL FILLED PE DD/MM/YYYY 001M-305M-500
PACKAGE	250m Wooden reel 500m Wooden reel
TEMPERATURE RATINGS	OPERATING TEMP. -40°C to +60°C (-40°F to +140°F) STORAGE TEMP.: -40°C to +75°C (-40°F to +167°F) INSTALLATION -20°C to +60°C (-4°F to +140°F)

TDS# MSEC C64PEXT GEL 23082016v2

Disclaimer: Although Maser Communications (Australia) Pty Ltd makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.