


INSTRUMENTATION CABLE 1.5mm² OS - BLUE

APPLICATION: Used in process control applications for interconnecting measurement instruments, instrument panels, sensing devices and control systems. These cables are not to be regarded as power cables and should not be used for the direct connection of equipment to mains power supplies.



TECHNICAL DATA

Conductor	Stranded Plain Annealed Copper Conductor 1.5mm ² (7/0.50)
Insulation	PVC, V-90, White & Black Numbered Twisted Pair
Screen	Overall Aluminium/Polyester Foil Shield with 7/0.20 Tinned Copper Drain Wire
Sheath	Blue PVC, 5V-90, Flame Retardant UV Resistant
Operating Voltage	110V AC/150V DC
Operating Temperature	-25°C to +75°C
Insulation Rating	300V
Bending Radius	8D
Standards	International: IEC 60332-3-22, IEC 60079.14 Australia/New Zealand: AS/NZS 1125, AS/NZS 3808, AS/NZS 1660

Maximum Current Rating (Amps)	13
Conductor Resistance @ 20°C (Ω/km)	13.6
Capacitance Cond. to Cond. - Unscreened (pf/m)	110
Capacitance Cond. to Cond. - Screened (pf/m)	200
Capacitance Cond. to Scr. - Screened (pf/m)	300
Characteristic Impedance @ 1kHz Unscreened (Ohms)	200
Characteristic Impedance @ Screened 1kHz (Ohms)	150
Inductance @ 1kHz (mH/km)	0.95
LR Ratio (uH/Ω)	36.5

PHYSICAL CHARACTERISTICS

Product Code	No. of Pairs	Conductor Area (mm ²)	Conductor Stranding (No./mm)	Insulation Thickness (mm)	Nominal O.D. (mm)	Approx. Weight (kg/km)
MAU5102CS BE	1	1.5	7/0.50	0.4	6.4	57
MAU5502CS BE	2	1.5	7/0.50	0.4	9.6	106
MAU5504CS BE	4	1.5	7/0.50	0.4	11.2	183
MAU5506CS BE	6	1.5	7/0.50	0.4	14.3	289
MAU5508CS BE	8	1.5	7/0.50	0.4	15.2	371
MAU5510CS BE	10	1.5	7/0.50	0.4	18.3	475
MAU5512CS BE	12	1.5	7/0.50	0.4	18.9	550
MAU5516CS BE	16	1.5	7/0.50	0.4	20.7	713
MAU5520CS BE	20	1.5	7/0.50	0.4	23.4	894
MAU5524CS BE	24	1.5	7/0.50	0.4	25.9	1057
MAU5536CS BE	36	1.5	7/0.50	0.4		
MAU5550CS BE	50	1.5	7/0.50	0.4		

Disclaimer: Although Maser Australia makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein