


# fibreflow™ Tube Distribution Closure (TDC)

Product Code 7514



## 1.0 DESIGN FEATURES

- Accepts fibreflow™ tube bundles and sub ducts up to 40mm (1.6”) in diameter
- One piece grommet and seal arrangement
- Manifold option allows 6 x 1DB to be dropped off from 1 port (shown above Product Code:7717)
- Captivated screws in lid portion allowing inverted installation
- Can be re-entered
- Can be retro-fitted to existing tube bundles/sub ducts
- Straight through, H and Y configurations possible
- IP67 rated (equivalent to NEMA 6)
- Lightweight - 1.2Kg (2.6lb)

## 2.0 APPLICATION

Tube Distribution Closure (TDC) can be Direct Buried into a waiting trench (following DB fibreflow™ installation procedures on back-fill) or placed inside a manhole or handhole.

## 3.0 TECHNICAL SPECIFICATION:

Materials:	Plastic shell
	All metallic parts Stainless Steel
Dimensions:	Length: 316mm (12.4”)
	Width: 220mm (8.7”)
	Height: 70mm (2.8”)
Colours:	All plastic parts to RAL6005 (moss green)
	Grommets & seal Black

## 4.0 QUALITY TESTS:

Impact:	1Kg (2.2lb) weight dropped from 1m (3.3feet)
Water Resistance:	Tested to IP67 (equivalent to NEMA 6)
Pull out:	Drop Port: >940N (>211 lbf)
	Other Ports: >1340N (>301 lbf)

This data sheet is intended as a guide only. Whilst the information it contains is believed to be correct, Emtelle can take no responsibility for actions taken based on the information contained in this document. Emtelle reserves the right to make changes to this document without notice. All sales of product are subject to Emtelle's terms and conditions of sale only, which can be found on Emtelle's website. This document is protected by copyright (c) Emtelle UK Limited [2005]. The products depicted are protected by intellectual property rights. Any unauthorized copying of this document or of our products is prohibited and Emtelle UK Limited will take action to prevent any infringement of its rights and to claim damages for the loss that it suffers.