


## INSTRUMENTATION CABLE 1.5mm<sup>2</sup> OS TRIADS - BLUE

**APPLICATION:** Used in process control applications for interconnecting measurement instruments, instrument panels, sensing devices and control systems. These cables are not to be regarded as power cables and should not be used for the direct connection of equipment to mains power supplies.



### TECHNICAL DATA

<b>Conductor</b>	Stranded Plain Annealed Copper Conductor 1.5mm <sup>2</sup> (7/0.50)
<b>Insulation</b>	PVC, V-90, Red, White & Black Numbered Twisted Triad
<b>Screen</b>	Overall Aluminium/Polyester Foil Shield with 7/0.20 Tinned Copper Drain Wire
<b>Sheath</b>	Blue PVC, 5V-90, Flame Retardant UV Resistant
<b>Operating Voltage</b>	110V AC/150V DC
<b>Operating Temperature</b>	-20°C to +90°C
<b>Bending Radius</b>	8D
<b>Standards</b>	International: IEC 60332-3-22, IEC 60079.14 Australia/New Zealand: AS/NZS 1125, AS/NZS 3808, AS/NZS 1660

<b>Maximum Current Rating (Amps)</b>	13
<b>Conductor Resistance @ 20°C (Ω/km)</b>	13.6
<b>Capacitance Cond. to Cond. - Unscreened (pf/m)</b>	110
<b>Capacitance Cond. to Cond. - Screened (pf/m)</b>	200
<b>Capacitance Cond. to Scr. - Screened (pf/m)</b>	300
<b>Characteristic Impedance @ 1kHz Unscreened (Ohms)</b>	200
<b>Characteristic Impedance @ Screened 1kHz (Ohms)</b>	150
<b>Inductance @ 1kHz (mH/km)</b>	0.95
<b>LR Ratio (uH/Ω)</b>	36.5

### PHYSICAL CHARACTERISTICS

Product Code	No. of Triads	Conductor Area (mm <sup>2</sup> )	Conductor Stranding (No./mm)	Insulation Thickness (mm)	Nominal O.D. (mm)	Approx. Weight (kg/km)
MAU5202CS BE	1	1.5	7/0.50	0.4	6.8	76
MAU5602CS BE	2	1.5	7/0.50	0.4	10.3	148
MAU5604CS BE	4	1.5	7/0.50	0.4	13.2	277
MAU5606CS BE	6	1.5	7/0.50	0.4	15.0	399
MAU5608CS BE	8	1.5	7/0.50	0.4	17.9	543
MAU5612CS BE	12	1.5	7/0.50	0.4	21.0	803

Disclaimer: Although Maser Australia makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein