


INSTRUMENTATION CABLE

0.5mm² OS - BLACK

NOT FOR MAINS CONNECTION

APPLICATION: Used in process control applications for interconnecting measurement instruments, instrument panels, sensing devices and control systems. These cables are not to be regarded as power cables and should not be used for the direct connection of equipment to mains power supplies.



TECHNICAL DATA

Conductor	Stranded Plain Annealed Copper Conductor 0.5mm ² (7/0.30)
Insulation	PVC, V-90HT, White & Black Numbered Twisted Pair
Screen	Overall Aluminium/Polyester Foil Shield with 7/0.20 Tinned Copper Drain Wire
Sheath	Black PVC, 5V-90, Flame Retardant UV Resistant
Operating Voltage	110V AC/150V DC
Operating Temperature	-20°C to +90°C
Bending Radius	8D
Standards	International: IEC 60332-3-22, IEC 60079.14 Australia/New Zealand: AS/NZS 1125, AS/NZS 3808, AS/NZS 1660

Maximum Current Rating (Amps)	3.2
Conductor Resistance @ 20°C (Ω/km)	38.4
Capacitance Cond. to Cond. - Unscreened (pf/m)	85
Capacitance Cond. to Cond. - Screened (pf/m)	145
Capacitance Cond. to Scr. - Screened (pf/m)	240
Characteristic Impedance @ 1kHz Unscreened (Ohms)	380
Characteristic Impedance @ Screened 1kHz (Ohms)	300
Inductance @ 1kHz (mH/km)	1.0
LR Ratio (uH/Ω)	13.7

PHYSICAL CHARACTERISTICS

Product Code	No. of Pairs	Conductor Area (mm ²)	Conductor Stranding (No./mm)	Insulation Thickness (mm)	Nominal O.D. (mm)	Approx. Weight (kg/km)
MAU5001CS	1	0.5	7/0.30	0.4	5.2	33
MAU5002CS	2	0.5	7/0.30	0.4	7.3	58
MAU5003CS	3	0.5	7/0.30	0.4	7.9	71
MAU5004CS	4	0.5	7/0.30	0.4	8.8	93
MAU5006CS	6	0.5	7/0.30	0.4	10.7	135
MAU5008CS	8	0.5	7/0.30	0.4	11.2	172
MAU5010CS	10	0.5	7/0.30	0.4	13.5	223
MAU5012CS	12	0.5	7/0.30	0.4	13.9	256
MAU5016CS	16	0.5	7/0.30	0.4	15.8	340
MAU5020CS	20	0.5	7/0.30	0.4	17.7	421
MAU5024CS	24	0.5	7/0.30	0.4	19.7	504
MAU5036CS	36	0.5	7/0.30	0.4		
MAU5050CS	50	0.5	7/0.30	0.4		

Disclaimer: Although Maser Australia makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein