

# DataGuard® (SWA)

LSZH FireFighter® 440Series Multi-Pair

24awg RS-485 Low Capacitance 600V



## Application

A range of 24awg multi-pair low capacitance cables with a high level of screening. Provides interference free, high speed data transmission suitable for RS485 applications. These cables utilise DataGuard® armouring and FireFighter® Low Smoke Zero Halogen performance materials.

## Cable Design

Conductor	Stranded tinned copper wire (24awg)
Insulation	see specification table
No. of Pairs	1, 2, 3, 4 or 8 - Colour coded to Chart 5
Overall Shield	Overall Aluminium/polyester tape
Drain Wire	Stranded tinned copper wire
Overall Braid Shield	Tinned copper wire braid, ≈ 90% coverage
Inner Jacket	LSZH FireFighter® SHF-1, Grey
Armour	DataGuard® Steel Wire Armour (DSWA)
Outer Jacket	LSZH FireFighter®, Black

## Characteristics

- Indoor/Outdoor applications
- Mechanical protection
- Rodent Protection
- UV-Resistant
- 600 V rated
- Temperature Range : -20°C up to +90°C

## Fire Behaviour

- Flame Retardant acc. to IEC 60332-1
- Halogen Free acc. to IEC 60754
- Smoke Emission acc. to IEC 61034



# DataGuard® (SWA)

LSZH FireFighter® 440Series Multi-Pair  
24awg RS-485 Low Capacitance 600V

## Specification

Part Number	Formation No. of Pairs	Insulation	Insulation Diameter mm	Nom. Inner Jacket Ø mm ± 10 %	Nom. Outer Jacket Ø mm ± 10 %	Weight kg/km
144401P2454	1 x 2 x 24 awg	PE	1,62	5,50	10,0	336
144402P2454	2 x 2 x 24 awg	PE	1,62	8,40	13,0	350
144403P2454	3 x 2 x 24 awg	PE	1,62	8,60	14,0	358
144404P2454	4 x 2 x 24 awg	PE	1,62	9,30	14,4	367
144408P2454	8 x 2 x 24 awg	Foam PE	1,15	10,0	15,0	406

## Electrical Characteristics

Nom. Capacitance (cond./cond.) pF/m	Nom. Capacitance (cond./cond./ screen) pF/m	Electrical Resistance Ω/km	Nom. Velocity of Propagation %	Nom. Inductance μH/m	Nom. Impedance Ω
42	75,5	82	66	0,56	120

Belcom Cables Ltd. ("Belcom") reserves the right to make changes to the product described in this specification without prior notice. Belcom does not assume any liability which may occur due to the use of the specification described herein. Drawings are not to scale unless otherwise specified and are provided for general and informational purposes only. All values represented in this specification should be used as a guide only and exact product details can be confirmed at point of enquiry.