


POWER & LIGHTING CONTROL CABLE 2C+E 2.5mm² + 2 Core 1.5mm² 450/750v

APPLICATION: For use in digital, addressable lighting control systems.



TECHNICAL DATA

Conductor	
• 2C+E 2.5mm ² Power Cable	7/0.67 Stranded Tinned Copper
• 2 Core 1.5mm ² Control Cable	19/0.32 Stranded Tinned Copper
Insulation	
• 2C+E 2.5mm ² Power Cable	V-90 PVC – Black, Red, Green/Yellow
• 2 Core 1.5mm ² Control Cable	V-90 PVC – Orange, Purple
Filler	
• 2C+E 2.5mm ² Power Cable	Filling Rope
• 2 Core 1.5mm ² Control Cable	N/A
Sheath	
• 2C+E 2.5mm ² Power Cable	5V-90 PVC – Orange
• 2 Core 1.5mm ² Control Cable	5V-90 PVC – Orange w/ Grey Stripe
Rated Voltage (Uo/U)	450V/750V
Max. DC Resistance @ 20°C (Ω/km)	
• 2C+E 2.5mm ² Power Cable	≤ 7.56
• 2 Core 1.5mm ² Control Cable	≤ 12.2
Operating Temperature	-20°C to +90°C
Standards	AS/NZS 5000.2, AS/NZS 1125, AS/NZS 3808, IEC 60332-1-2 EESS: GMA-525068-EA Compliant to BEP PVC Best Practice (Greenstar)

PHYSICAL CHARACTERISTICS

Product Code	No. of Cores	Conductor Area (mm ²)	Insulation Thickness (mm)	Nominal O.D. (mm)	Reel Quantity (m)	Package Dimensions (LxWxH)	Package Weight (kg)
MAS2C3G2.5	2C+E (Power) 2 Core (Control)	2.5 1.5	0.7 0.6	18.4 x 10.2	200	43 x 43 x 33cm	53.0

Disclaimer: Although Maser Australia makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.