



R.U.C.K

PowerHUB AIR

RUGGED UNIVERSAL CHARGE KIT **REMAIN COMBAT EFFECTIVE**

R.U.C.K PowerHUB AIR

PATENT PENDING

Powers all devices at the tactical edge using standard and in-service **BB-2590 / 5590 / 390** series batteries as your power source.

This enables you to use standard AC mains 3 pin power cables equipment to power any MOTS/COTS equipment in any environment.

Simply connect your standard mains power cable to any of the units internal or external 3 pin plug sockets to run devices or systems in low or nil infrastructure environments and hot-swap out batteries as required without losing power.

R.U.C.K PowerHUB AIR delivers continuous 1350W, (1600W Peak) 220V AC housed within a fully ruggedised enclosure to power and re-charge multiple devices as required.

Charge and power all devices irrespective of OEM from Satcom terminals, Radio, Comms Systems, Drones, EUD's, PC's, GCS's, EPM's/ECM's, NVG's, etc

R.U.C.K PowerHUB AIR will convert power from your standard issue Mil batteries to power anything which uses mains AC power in the field.



Key Features

- Provides 220-230 V mains output and sockets using **BB-2590 / 5590 / 390** batteries
- If using 8 x BB-2590 batteries unit will provide 2300 kWh capacity (*1-8 qty of batteries can be used as available)
- Batteries hot-swappable for continuous AC power supply
- Individual low-voltage battery status indicator for each battery slot
- 3 x Internal UK AC mains 3 pin power outlets + 4 x USB outlets
- 1 x External UK AC mains 3 pin power outlet
- Fast charging capability via USB Type-A and USB Type-C outputs
- Fixing/mounting options to fix the case down vehicles/ platforms
- Batteries are protected from dust, debris and moisture ingress
- Suitable for powering and charging battlefield electronics with USB interfaces as well as AC mains (3-Pin) devices
- Ruggedised enclosure for harsh military environments
- Air-safe; Removeable batteries enabling easy transportation by Mil or Civ carriers

Specification

Power Input

Up to 8 x BB-2590 or 5590/390 removeable batteries

Power Capacity

Dependent on quantity & batteries used
If using 8 X BB-2590/U- 2300 kWh capacity

AC Power Output (*Using 8 x BB-2590/U batteries)

220-230V Output voltage
1350W max total continuous output
Pulse output 2000W <5 seconds
4 X UK Mains Sockets + 4 x USB Ports

AC Power Output (*Using 8 x BA-5590/U batteries)

220-230V Output Voltage
320W output
4 X UK Mains Sockets + 4 x USB Ports

USB Outputs x 4

USB-C-5V 3A, 9V 2.22A, 12V 1.67A (PD20W) x 2
USB-A-5V 3.1A x 2

Physical

Dimensions (LxWxH) 645x508x368mm
Case Colour: Black
Mass (kg)- 27Kg



Environmental and Safety

Dust and Water (Lid closed)	IP64
Storage Temperature	-20-75°C
Operating Temperature	0-55°C

CE, ROHS, REACH, Overcurrent (OCP), Overtemperature (OTP)



Contact us




01425 561792



INFO@KINECTEDSOLUTIONS.CO.UK



KINECTEDSOLUTIONS.CO.UK



#Staykinected